

## FIRE BOWL



### Details

The Firebowl has the sentiment of a traditional campfire, without the tireless back bending and fabric clinging smoke! Adding an authentic ambience to any atmosphere, the fire bowl is portable and convenient.

### Product Specifications

- **Includes:** pre-attached 10' hose with regulator, propane tank stabilizer ring, and decorative rock set
- **Heat output:** 58,000 BTU/h, with use of 20lb propane tank
- **Dimensions:** L 19" x W 19" x H 11"
- **Weight:** 20lbs

### Important Information

- This appliance shall be used only outdoors in a well-ventilated space and shall not be used in a building, tent, garage or any other enclosed area.
- Turn gas off when not in use.
- Minimum clearances: (Bottom: Non-combustible surface) (Top: 80") (Side: 30")
- If this appliance is not in use, the gas must be turned off at the supply cylinder.
- Ensure that the LP gas cylinder is kept at a minimum distance of three feet (36 inches) away from the appliance.

### Installation Instructions

- Ensure that unit valve dial is in the "OFF" position by pushing and turning clockwise until the dial stops.
- Securely attach regulator (large end of hose) to your propane cylinder.
- Extend hose to full length and ensure that the propane tank is as far as safely possible from the Firebowl and place the tank in the included stabilizer ring.
- Leak Test all connections.
- Slowly turn cylinder valve to the open position.
- Using a lighter or match, ignite lighter and hold flame slightly above the burner, then open the valve on the appliance slowly by turning (counter-clockwise) until the unit ignites.
- Once the unit is burning normally set the dial to desired flame height.

\*Please see enclosed manufacturer's instructions for more detailed instructions and troubleshooting.